

**MODULE 05**

**FOR A1 LEVEL CERTIFICATION**

# **ELECTRONIC INSTRUMENT SYSTEMS**

James W. Wasson, PhD., Author

## **Aviation Maintenance Technician Certification Series**



72413 U.S. Hwy 40  
Tabernash, CO 80478-0270 USA

[www.actechbooks.com](http://www.actechbooks.com)

+1 970 726-5111

**AVAILABLE IN**  
*Printed Edition and Electronic  
(eBook) Format*



## AVIATION MAINTENANCE TECHNICIAN CERTIFICATION SERIES

Author James W. Wasson, PhD.  
Layout/Design Michael Amrine

Version 002.1 - Effective Date 09.29.2021

Copyright © 2016, 2019 — Aircraft Technical Book Company. All Rights Reserved.

No part of this publication may be reproduced, stored in a retrieval system, transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the prior written permission of the publisher.

To order books or for Customer Service, please call +1 970 726-5111.

[www.actechbooks.com](http://www.actechbooks.com)

Printed in the United States of America

ISBN: 978-1951275037



9 781951 275037

For comments or suggestions about this book, please call or write to:  
1.970.726.5111 | [comments@actechbooks.com](mailto:comments@actechbooks.com)

# WELCOME

The publishers of this Aviation Maintenance Technician Certification Series welcome you to the world of aviation maintenance. As you move towards EASA certification, you are required to gain suitable knowledge and experience in your chosen area. Qualification on basic subjects for each aircraft maintenance license category or subcategory is accomplished in accordance with the following matrix. Where applicable, subjects are indicated by an "X" in the column below the license heading.

For other educational tools created to prepare candidates for licensure, contact Aircraft Technical Book Company.

We wish you good luck and success in your studies and in your aviation career!

## REVISION LOG

VERSION	EFFECTIVE DATE	DESCRIPTION OF CHANGE
001	2014 09	Module Creation and Release
002	2019 05	Fine tuned Sub-Module content sequence based on Appendix-A. Updated layout and styling.
002.1	2021 09	Added enhanced Welcome, Forward, EASA License and General Knowledge Requirements. No content changes.



# DIGITAL TECHNIQUES ELECTRONIC INSTRUMENTS

## ELECTRONIC INSTRUMENT SYSTEMS

### SUB-MODULE 01

#### PART-66 SYLLABUS LEVELS

CERTIFICATION CATEGORY →

A

#### Sub-Module 01

#### ELECTRONIC INSTRUMENT SYSTEMS

#### Knowledge Requirements

##### 5.1 Electronic Instrument Systems

Typical systems arrangements and cockpit layout of electronic instrument systems.

1

#### Level 1

A familiarization with the principal elements of the subject.

#### Objectives:

- (a) The applicant should be familiar with the basic elements of the subject.
- (b) The applicant should be able to give a simple description of the whole subject, using common words and examples.
- (c) The applicant should be able to use typical terms.

# ELECTRONIC INSTRUMENT SYSTEMS

## ANALOG INSTRUMENTS

Instruments that aid the pilot in controlling the altitude, attitude, airspeed and heading of the aircraft are known as flight instruments. Since the early days of flight there have been four basic flight instruments that have formed the well-known “T” arrangement located in the center of the instrument panel, as shown in *Figure 1-1*. These four basic instruments are 1) the airspeed indicator, located on the top left, that measures the aircraft’s speed in nautical miles per hour; 2) the attitude indicator, located on top center, that shows the aircraft’s attitude relative to the earth’s horizon; 3) the altimeter, on the top right, that displays the barometric altitude as measured in feet; and 4) the gyro-slaved heading indicator, in the bottom center, which shows which direction the aircraft is flying. These 4 basic flight instruments are typically augmented with a turn-and-bank indicator that displays the rate of turn in the roll axis and amount of bank in the yaw axis, and a vertical speed indicator that displays the rate of ascent or descent in feet per minute.

Assuming that the aircraft has radio navigation aids, it will also come equipped with a Radio Magnetic Indicator (RMI) coupled to an Automatic Direction Finder (ADF), and a Course Deviation Indicator (CDI) driven by VHF Omnidirectional Range (VOR) and Instrument Landing System (ILS) receivers. The ILS receiver drives the glide scope needle to set the glide path on an instrument approach and localizer needle provides lateral guidance to the center of the runway. These early flight instruments were analog meaning that they contained either mechanical or electro-mechanical rotating mechanisms to drive the pointer dials on the

instruments. For example, an analog airspeed indicator receives air pressure from the pitot tube, which expands a bellows that turns the dial on the indicator. With a digital system, the pitot air pressure enters an air data computer that converts the analog information into a digital data stream. Digital data is then sent to the airspeed indicator via an aircraft data bus where the data is converted back into analog signals to drive a pointer dial and/or is displayed digitally in numbers.

## DIGITAL INSTRUMENTS

With the advent of digital electronics in the early 1970’s, Electronic Instrument Systems, also known as “glass cockpits”, evolved that were more much more reliable than mechanical or electro-mechanical analog instruments, and had the advantage of combining several flight and navigation functions into one display to provide the crew with greater situational awareness.

The first commercial transport aircraft to employ an Electronic Instrument System (EIS) was the McDonnell Douglas MD-80 in 1979. The EIS on the MD-80 used Cathode Ray Tube (CRT) technology. However, during the next 10 years, Liquid Crystal Display (LCD) technology matured thereby replacing CRTs. Flat-panel LCDs are lighter than CRT displays, require less volume, and consume less electrical power, thereby generating less cockpit heat. Glass cockpit configurations vary widely between aircraft models from a single flight and navigation display in a small private aircraft to five or more LCD displays in a commercial transport aircraft. (*Figure 1-2*)



Figure 1-1. Basic Analog Cockpit Flight Instruments.



Figure 1-2. Airbus A380 EIS with 8 Large LCD Displays.



## ELECTRONIC DISPLAYS

The early EIS displays mimicked the analog display formats for ease in pilot training as the crew transitioned from older analog displays to digital displays that were driven by aircraft data computers, known as display processors or symbol generators.

**Figure 1-3** depicts an early model Boeing 737 instrument panel with an analog Attitude Direction Indicator (ADI) and analog Horizontal Situation Display (HSI) in the left picture, and a later model B737 instrument panel with electronic ADI (EADI) and electronic HSI (EHSI) displays shown in the right picture.

The ADI or EADI is an artificial horizon with lateral bars superimposed to display computer-generated pitch and bank steering commands from the Flight Director computer. The HSI or EHSI is similar to a heading indicator, except that it combines navigation commands from the VHF Omni-Range (VOR) or Global Positioning System (GPS) receivers, which are used for en-route guidance, or from the Instrument Landing System (ILS), which is used for terminal guidance. Besides heading, the HSI/EHSI also provides actual track, desired track, track angle error, drift angle, cross-track deviation, and distance to destination information, from the Distance Measuring Equipment (DME) or Inertial Navigation System (INS). (**Figure 1-4**)

The pilot and the co-pilot not only have independent EADI and EHSI displays, but they also have independent Display Processor Units, also known as Symbol Generators, to drive their displays (**Figure 1-5**).

Display formats are produced by the Symbol Generators that receive inputs from the crew and various on-board systems.

The Flight Director Systems, Navigation Systems, Air Data Systems, and Weather Radar provide inputs to the Symbol Generators, along with commands from the each crewmember's display control panel. The Symbol Generators produce the graphics for the EADI, EHSI, and an optional Multi-Function Display (MFD) that is mounted in the center instrument panel. The MFD, which is physically identical to the EADI and EHSI, is typically used to display weather radar information; however, it can also be used to display either flight information or navigational information in the event of an EADI or EHSI failure. The following section will discuss the Boeing 777 EIS, which is a more advanced example of the one just covered.

## ELECTRONIC FLIGHT INSTRUMENT SYSTEM

The Boeing 777, which first entered service in 1995, has six 8" × 8" multi-color LCD displays as shown in **Figure 1-6**. The B777 EIS consists of a dual-redundant Electronic Flight Instrument Systems (EFIS) and Engine Indication and Crew Alerting System (EICAS).

On the left side of the instrument panel is the Captain's EFIS, consisting of a Primary Flight Display (PFD) located outboard and a Navigation Display (ND) located inboard. The Co-Pilot's EFIS located on the right instrument panel has an identical PFD and ND, located outboard and inboard respectively. All the displays are interchangeable to reduce the number of required spares.



Figure 1-3. Equivalent Electromechanical Flight and Navigation Instruments on the left.




Figure 1-4. Typical EADI (top) and EHSI (bottom) Display Symbology

The information shown on each display, whether for flight or navigation, is determined by what each crew member selects on their individual display control panels.

The PFD takes the place of the EADI and displays all the information critical to flight, including attitude, airspeed, barometric altitude, vertical speed, heading, flight modes, radio altitude, ILS data, and Traffic Alert and Collision Avoidance System (TCAS) resolution advisory. The PFDs are designed to increase the crew's situational awareness by integrating all of this information into a single composite display instead of the crew having to monitor several independent analog

instruments. Also, the colors on the display change to alert the crew to potentially hazardous flight conditions, such as low airspeed, high rate of descent, etc.

**Figure 1-7** is a typical Primary Flight Display format showing the artificial horizon in the center of the display, airspeed on the left side, altitude on the right side, heading on the bottom, and flight modes on the top of the display. Notice how the moving ladder format used for altitude and airspeed provide both absolute and relative information so the crew knows not only the exact numeric value, but also the rate that the altitude and airspeed is changing.




Figure 1-5. Electronic Displays are driven by Symbol Generators.




Figure 1-6. Boeing 777 Electronic Instrument System has 6 LCD Displays.

The Navigation Display, shown in **Figure 1-8**, takes the place of the EHSI display to show the requisite information to navigate the aircraft, including heading, VOR, GPS, and ILS guidance. The ND has the ability to overlay additional information on the navigation page to eliminate the need for separate dedicated displays. Some examples of information that is typically overlaid on the ND include weather information from either the onboard weather radar or ground based sensors, and digital maps showing pre-programmed routes and waypoints from the Flight Management System.

## ENGINE INDICATION AND CREW ALERTING SYSTEM

The Engine Indication and Crew Alerting System (EICAS), also called an Electronic Centralized Aircraft Monitor (ECAM) on Airbus aircraft, performs the monitoring of aircraft systems that was previously performed by the Flight Engineer in three crew member cockpits. As previously shown in **Figure 1-6**, the two EICAS displays on the B777 are located in the center instrument panel. The upper EICAS display shows engine performance data, such as pressure ratio, N1 rotor






Figure 1-7. Primary flight display format.

speed, exhaust gas temperature, total air temperature, thrust mode, etc., in addition to cabin pressure, flap/slat position, landing gear position, and crew status alerts. (Figure 1-9)

The EICAS engine display format mimics the round analog instruments, while also providing digital readouts of the parameters. EICAS improves situational awareness by allowing the crew to see systems operation in graphical format and alerting them to any failures or impending failures. For example, if low oil pressure is detected, the EICAS will provide an aural alert and show to the oil pressure page on a lower display with a red box outlining which engine has low oil pressure.

The Airbus ECAM system provides the crew with the following levels of warning along with detailed messages as to the nature of the problem and suggested courses of action.




Figure 1-8. Navigation map display format.



Figure 1-9. EICAS engine display format.

- Level 3: An overspeed, fire, or stall condition will cause a repetitive chime aural warning with a bright red flashing light.

- Level 2: A system failure, but not a safety of flight issue, will result in a single chime aural warning and a steady amber light.
- Level 1: Failure leading to system degradation results only in an amber light.
- Mode or System Status: If everything is normal, a green light will illuminate.

The lower EICAS display is called a Multi-Function Display because it provides auxiliary information to the flight crew and maintenance crew. The MFD can be used as a secondary engine display, status display, communications display, maintenance page, or electronic checklist. The MFD formats also include synoptic displays that provide system status diagrams for the fuel, electrical, hydraulic, flight control, and environmental control systems, in addition to showing door and landing gear positions. On some aircraft, the MFD is also used to display images from the ground maneuvering camera system.




Figure 1-10. EICAS schematic diagram.

**Figure 1-10** is a schematic diagram of an Engine Indication and Crew Alerting System with all its associated components. The display select panel allows the crew to choose which computer is actively supplying information. It also controls the display of secondary engine information and system status displays on the lower monitor.

EICAS has a unique feature that automatically records the parameters of a failure event to be regarded afterwards by maintenance personnel. Pilots that suspect a problem may be occurring during flight can press the event record button on the display select panel. This also records the parameters for that flight period to be studied later by maintenance. Hydraulic, electrical, environmental, performance, and Auxiliary Power Unit (APU) data are examples of what may be recorded. EICAS uses Built-In-Test Equipment (BITE) for systems and components.

A maintenance control panel is included for technicians. When the aircraft is on the ground, push-button switches display information pertinent to various systems for analysis. (**Figure 1-11**)

This *sub-module* contained an overview of a state-of-the-art aircraft cockpit with its Electronic Instrument System. The following chapters will discuss how digital data streams are formed and processed by aircraft computers and then sent over digital data buses to cockpit displays to provide essential information for the flight crew and maintenance crew.




Figure 1-11. EICAS maintenance control panel.